

# acar

# X8

SCHUKO



Glossy surface

High quality power cord  
H05VV-F

8 socket outlets with earthing contacts  
with safety shutters for protection against electric shock

Slow blow automatic fuse

Illuminated double pole mains switch



acar

**acar**<sup>®</sup>

# acar X8 Schuko

Surge protective power strip

**8 SOCKET OUTLETS WITH EARTHING CONTACTS****AUTOMATIC FUSE****SOCKET OUTLETS SAFE FOR CHILDREN****ILLUMINATED DOUBLE POLE MAINS SWITCH****SURGE PROTECTION****3 AVAILABLE COLOUR VARIANTS****AVAILABLE POWER CORD LENGTHS: 1.5m, 3m, 5m**

ILLUMINATED DOUBLE POLE MAINS SWITCH



SURGE PROTECTION



SLOW BLOW AUTOMATIC FUSE



8 SOCKETS 10A WITH EARTHING CONTACTS AND SAFETY SHUTTERS



FOUR POSSIBLE WAYS OF POWER CABLE ROUTING AND OPTIONAL MOUNTING BRACKETS



The **acar X8 Schuko** is the latest surge protective power strip sold under the brand name acar. Reliability, efficient construction solutions and modern design allow us to provide a 5-year warranty for the **acar X8 Schuko**. The glossy surface emphasizes the uniqueness and fresh look of the product, making it visually eye-catching. Eight Schuko socket outlets and optimal size make the power strip useful both at home and in the office. The automatic fuse provides practically maintenance-free operation. High efficiency predispose the power strip to become the basic surge protection necessary everywhere. Modern and stylish design allows you to place it in any convenient and prominent place (desk, cabinet), its slender casing takes up a little space. The mounting brackets are available from dealers.

**Technical data: acar X8 Schuko**

Maximum load	$P_{MAX}$ 2300W
Nominal voltage $U_N$	230V
Nominal frequency	50Hz
Nominal load current	$\Sigma I_N = 10A$ MAX
Surge protection response time	<25ns
Maximum voltage $U_C$	250V 50Hz
Protection level $U_p$	$\leq 1.3kV$
Nominal discharge current $i_N$	2kA (L/N) – 8/20 $\mu s$
Maximum discharge current $i_{MAX}$	6.5kA (L/N) – 8/20 $\mu s$
Fuses	1 automatic fuse, slow blow 10A/250V
Anti-shock protection system	earthing contacts connected to the protective earthing conductor
Number of socket outlets	8 two-pole socket outlets with earthing contacts, 10A/250V
Switch	illuminated double pole mains switch
Housing	made of self-extinguishing plastic
Dimensions	445x56x47mm
Weight	kg

The manufacturer reserves the right to change the technical parameters of the device, resulting from technological progress.  
ATTENTION! The technical data define the maximum values of surges against which the device protects.